sen si

Sensi[™] Touch Smart Thermostat

Best Overall Smart Thermostat 2019.



Designed with you in mind. Easy install for you, upgraded features and convenient comfort for your homeowners. It's contractor-tested and homeowner-approved.

HD COLOR TOUCH SCREEN

The high-definition color display features easy-to-read temperatures and intuitive menus.

SAVE ABOUT 23% ON HVAC ENERGY¹

With features like geofencing, flexible scheduling and remote access, homeowners can save money without compromising their comfort.

HUMIDITY CONTROL

Help homeowners stay comfortable with humidification/ dehumidification control.

SMART ALERTS

Notifies homeowners of extreme temperature or humidity levels.

SMART HOME COMPATIBLE

Compatible with smart home platforms Amazon Alexa, the Google Assistant, Apple HomeKit* and Wink.



EASY TO INSTALL

Installation made simple with built-in level, illuminated backplate and easy-click terminals.

Easy step-by-step guide in the app to connect to Wi-Fi.

CONTRACTOR-ON-CALL

The Sensi app stores your contact information so when your customer needs service, you're just a tap away. Register at **sensiregistration.com**.

MULTIPLE THERMOSTAT CONTROL

Easy management for schools and light commercial applications.

CIRCULATING FAN

Improves air quality when a custom run time is set.



Use of the Works with Apple HomeKit logo means that an electronic accessory has been designed to connect specifically to iPod touch, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Apple in to control this HomeKit enabled accessory automatically and away from home, an Apple T with tvOS 10.0 or later or an iPad with iOS 10.0 or later on iPad with iOS 10.0 or later or an iPad with iOS 10.0 or late



Theregy savings calculated by comparing operation time for a nationwide sample of Sensi users with temperature adjustments averaging 40 vs. users with no djustments. Savings vary based on equipment type/condition, insulation, climate & temperature adjustment size/frequency.





1F95U-42WFB

1F95U-42WF



DID YOU KNOW?

Jp to 85% of Sensi customers replaced a working thermostat**

Sensi Touch Smart Thermostat 1F95U-42WF 1F95U-42WFB

MAKING INSTALLATION EVEN EASIER

- Built-in level for picture-perfect mounting
- Terminal lights for increased visibility while wiring
- Large, easy-to-read terminal labels on the back plate
- Easy-click terminals, eliminating the need for a screwdriver
- Size that covers the existing footprint of most thermostats



SPECIFICATIONS

ELECTRICAL RATING

20 to 30 VAC, 50/60 Hz 1.5 Amps maximum per terminal 2.5 Amps maximum (all terminals combined)

STANDARD SYSTEMS

Single-stage gas, oil, electric Single-stage heat pump Multi-stage gas, oil, electric Multi-stage heat pump

SETPOINT RANGE 50°F to 99°F (10°C to 36°C)

ACCESSORIES

Wallplate: (white) F61-2689 (6.75" x 4.50") Wallplate: (black) SA5B (6.75" X 4.50") Thermostat guard: F29-0198

RATED DIFFERENTIALS (@ 6°F / HR) Fast

Heat (conventional gas/oil/elect): Cool (central air): Heat pump (heat and cool): Heat pump (aux):

COMPATIBILITY

Conventional heating and cooling systems:

Heat pump*, heat only and cool only systems:

SENSI ALERT

High temperature: Low temperature: High humidity: Loss of heat/cool:
 Fast
 Med
 Slow

 0.5°F
 0.75°F
 1.9°F

 0.9°F
 1.2°F
 1.7°F

 0.9°F
 1.2°F
 1.7°F

 0.5°F
 0.75°F
 1.9°F

Power Source Hardwired only (c-wire)

Hardwired only (c-wire)

Trigger Above 99°F Below 45°F Above 70% Temp goes up or

down 5°F during cycle

DIMENSIONS

5.63["] W x 3.38["] H x 1.00" D

STORAGE

-20° to 150°F (-29° to 65°C) 0%-90% RH non-condensing

OPERATING AMBIENT 32°F to +105°F

(0°C to +41°C)

OPERATING HUMIDITY 90% non-condensing max

DISPLAY TEMPERATURE RANGE 32°F to +99°F (0°C to 37°C)

USAGE REPORTS

ENERGY STAR CERTIFIED

*The Sensi thermostat provides automatic dual fuel control without an outdoor sensor. A fossil fuel kit may be added if user selectable balance point settings are desired.

Model	Program Options		Max Stages Heat/Cool		Applications			Power Source		Selectable Performance Features							Comfort & Convenience Features									
Model Number	Wi-Fi Control/Smart Home Qualified	7 Day	Non- Programmable	Conventional	Heat Pump	Gas/Oil/Electric	3 Wire Zone	Millivolt	PTAC Compatible	Battery	Hardwired (24V)	Auto Changover	Circulating Fan	EMR/ Early Start Program	Temperature Limits	Humidity Display	Dual Fuel Control	Remote Sensor	Filter Change Reminder	Auto DST Adjust	Keypad Lockout	Cont. backglow w/ Common	Permanent Memory	Usage Reports	Energy Star Certified	Hum/Dehum Control
1F95U-42WF	٠	٠	٠	2/2	4/2	•	٠		۰		•	•	٠	۰		٠	٠			۰	•	•	•	•	۰	۰
1F95U-42WFB	٠	۰	٠	2/2	4/2	٠	۰		۰		•	•	۰	•		۰	٠			۰	•	•	٠	٠	۰	•

TERMINAL DESIGNATIONS RC RH



‡Thermostat has internal jumper on RC and RH. On two transformer systems, clip red jumper wire on thermostat.

emerson.com/sensipro

