

CR20K6-PFV

HCFC, R-22, 60 Hz, 1 -phase, 208/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45.00	45.00
Condensing Temp. (°F)	130.00	100.00
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (Btu/hr)	19600	26300
Power (W):	1830	1490
Current (Amps):	8.20	6.80
EER (Btu/Wh):	10.70	17.70
Mass Flow (lbs/hr):	287	339
<u>Sound Data @</u>		
Sound Power (dBA):	71 Avg	76 Max
Vibration mils(peak-peak):	1.6 Avg	2.6 Max
Record Date:	1993-06-18	

Electrical

LRA High*(Amp):	50.0
LRA Low* (Amp):	
LRA Half Winding (Amp):	
MCC (Amps):	14.9
Max Operating Current(Amp):	3500
RLA, MCC/1.4;use for contactor selection (Amp):	10.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	9.6
RPM:	
UL File No:	
UL File Date:	28-Dec-1984
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacment (in ³ /Rev):	2.23
Displacment (ft ³ /hr):	270.64
Overall Length (in):	10.23
Overall Width (in):	9.65
Overall Height (in):	13.19
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	13.56 *
Suction Size (in),Type:	3/4 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	45
Oil Recharge (oz):	43
Net Weight (lbs):	61.00
Internal Free Volume (in ³):	450.00
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-04	145.0	175.0	220	HIGH TORQUE
Start Capacitor	014-0061-16	43.0	52.0	330	LOW TORQUE
Run Capacitor	014-0064-06	30.0	0.0	370	

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
--------------------	----------------	--------------	------------------	--------------------