



Typical Application: US Unitary Air-Conditioner

R410A 1φ 208-230V / 60Hz

Testing Condition : ASHRAE/T
CHEER

Model	Disp.		Capacitor		Cooling Capacity		Input Power		EER	COP	Outline Drawing	Safety Approval					
	c.c.	μ F	VAC	Btu/h	W	W	Btu/h.W	W/W	C-UL	VPC		TUV	CCC	VDE	Others		
50N282X	11.4	30	370	11350	3325	1145	9.91	2.90	50-04(b)	☉							
				13650	3995	825	16.55	4.84									
50N382X	14.9	35	370	15275	4475	1480	10.32	3.02	50-04(b)	☉							
				18590	5445	1080	17.21	5.04									
50N382Z	14.9	35	370	15235	4460	1460	10.43	3.05	50-12								
				18570	5440	1040	17.86	5.23									
50N492X	19.2	40	370	19640	5750	1890	10.39	3.04	50-04((b)								
				24285	7110	1385	17.53	5.13									
50N492Z	19.2	45	370	19325	5660	1900	10.17	2.98	50-04(b)	☉							
				24005	7030	1325	18.12	5.31									
50N4929	19.2	45	370	19245	5635	1870	10.29	3.01	50-12								
				23810	6970	1300	18.32	5.36									
50N512X	19.7	40	370	20040	5870	1980	10.12	2.96	50-04((b)								
				24920	7295	1430	17.43	5.10									
50N6229	24.2	50	370	24325	7125	2410	10.09	2.96	50-12								
				30555	8945	1680	18.19	5.32									

