



MODEL NUMBER:
CF-521002-LED-10 (BRUSHED NICKEL)
CF-521002-LED-20 (OIL RUBBED BRONZE)
CF-521002-LED-30 (WHITE)
CF-521002-LED-40 (BLACK)

52 in. Windsome Ceiling Fan



- 52 in. Sweep 5 Blades
- 188 mm X 15 mm Silicon Steel Motor
- 13 degree Blade Pitch
- Triple Capacitor, Dry Location
- 3-Speed Reversible Direction
- Single-Unit Housing with LED Light Kit
- 19 Watt Dimmable Soft-White Light (3,000K)
- Compliant with DOE and CEC Energy Efficiency Regulations
- Limited Lifetime Warranty (fan motor only)

SPECIFICATIONS

| | |
|---------------------------------------|--|
| ITEM NUMBER | CF-521002-LED-XX |
| FINISH | Brushed Nickel, Oil Rubbed Bronze, White, Black |
| CATEGORY | Ceiling Fan |
| INDOOR/OUTDOOR | Indoor |
| BLADE MATERIAL | Plywood |
| BLADE FINISH OPTIONS | Chrome, Rosewood, Black Gloss/Rosewood, Silver Oak/Rosewood, Black Forest/Rosewood |
| DIMENSIONS | 52 in. x 16.3 in. |
| NUMBER OF BLADES | 5 |
| MOTOR SPECS | 188 mm x 15 mm AC |
| CONTROLS | Pull Chain Switch |
| DOWN ROD | 6 in. |
| LEAD WIRE | 80 in. |
| BLADE PITCH | 13 deg. |
| BLADES LOWEST POINT TO CEILING | 12.6 in. |
| LIGHT KIT | LED Module |
| SHADE MATERIAL | Glass |
| SHADE DESCRIPTION | Frosted Opal Glass |
| NUMBER OF SHADES | 1 |
| SHADE DIMENSIONS | 10 in. Dia. x 3.1 in Depth |

PERFORMANCE

| | | | |
|-----------------------------------|-------------------------|---------------|-------------|
| WATTAGE | 19 W | | |
| COLOR TEMP | 3000K | | |
| CRI | ≥90 | | |
| INITIAL LUMENS | 1600lm | | |
| DELIVERED LUMENS | | | |
| BULB/LED INCLUDED | Yes | | |
| DIMMABLE | Yes | | |
| OPERATING VOLTAGE | 120V, 60Hz | | |
| HARDWARE FINISH OPTIONS | ORB, White, Black, ST | | |
| LABELS | ETL Dry Location Listed | | |
| | LOW | MEDIUM | HIGH |
| RPM | 57-63 | 109-115 | 163-172 |
| AMPS | 0.26 | 0.42 | 0.62 |
| WATTS | 12.56 | 34 | 73.90 |
| AVERAGE AIRFLOW (CFM AVE.) | 3970 | | |
| AIRFLOW EFFICIENCY (CFM/W) | 88 | | |