

MODEL NUMBER: CF-521011-LED-10 (BRUSHED NICKEL) CF-521011-LED-20 (OIL RUBBED BRONZE) CF-521011-LED-30 (WHITE) CF-521011-LED-40 (BLACK)

52 in. Tramontana Ceiling Fan

With "Quick Connect" blade installation feature.



- 52 in. Sweep 5 Blades
- 153 mm X 13 mm Silicon Steel Motor
- 12 degree Blade Pitch
- Triple Capacitor, Dry Location
- Frosted White Glass Dome
- 3 LED 9 Watt Soft-White Bulbs
- Compliant with DOE and CEC Energy Efficiency Regulations
- Limited Lifetime Warranty (Fan Motor Only)
- Classic Look Ceiling Mount

SPECIFICATIONS

ITEM NUMBER	CF-521011-LED-XX	
FINISH	Brushed Nickel, Oil Rubbed Bronze, White, Black	
CATEGORY	Ceiling Fan	
INDOOR/OUTDOOR	Indoor	
BLADE MATERIAL	MDF	
BLADE FINISH OPTIONS	Chrome, Rosewood, Black Gloss/ Rosewood, Silver Oak/Rosewood, Black Forest/Rosewood	
DIMENSIONS	52 in. x 18.88 in.	
NUMBER OF BLADES	5	
MOTOR SPECS	153 mm x 13 mm AC	
CONTROLS	Pull Chain Switch	
DOWN ROD	4.5 in.	
LEAD WIRE	80 in.	
BLADE PITCH	12 deg.	
BLADES LOWEST POINT TO CEILING	13 in.	
LIGHT KIT	E26 x 3	
SHADE MATERIAL	Glass	
SHADE DESCRIPTION	Frosted Opal Glass	
NUMBER OF SHADES	1	
SHADE DIMENSIONS	12 in. Dia. x 3.9 in Depth	

PERFORMANCE

WATTAGE		9.5 W x 3		
COLOR TE	MP	3000K		
CRI		≥90		
INITIAL LUMENS		800lm		
DELIVERED LUMENS				
BULB/LED	INCLUDED	Yes		
DIMMABLE	<u>-</u>	No		
OPERATIN	G VOLTAGE	E 120V, 60Hz		
HARDWARE FINISH OPTIONS		ORB, White, Black, ST		
LABELS		ETL Dry Loca	rion Listed	
	LOW	MEDIUM	HIGH	
RPM	64-68	115-128	174-180	
AMPS	0.22	0.35	0.51	
WATTS	10.54	28.5	60.8	
AVERAGE AIRFLOW (CFM AVE.)		3280		
AIRFLOW EFFICIENCY (CFM/W)		88		