

Sturbridge Flat Ball Series



Features & Options

Door Thickness – Fit 1-3/8" to 1-3/4" standard door thickness

Door Preparation – Cross Bore: 2-1/8", Edge: 1"

Latch Backset – Adjustable 2-3/8" – 2-3/4"

Latch – 2-way

Standard Latch Faceplate – 1" x 2-1/4" Radius

Spindle Type – Crescent

Bolt – 1/2" throw

Cylinder – Zinc alloy cylinder KW1 keyway 5-pin

Standard Strike Plate – 2-1/4" x 1-3/4" round corner full lip

Material – Steel, Brass and Zinc

ANSI/BHMA – A156.2 Grade 3

Functions

Entry – (F109)

Both lever locked or unlocked by key outside or turn-piece inside

Passage – (F75)

Latchbolt operated by lever from either side at all times

Privacy – (F76)

Both levers locked or unlocked by turn-piece inside. Outside lever unlocked by coin or screwdriver

Dummy

Pull one/both side, no mechanical operation

Part

Description

55028	Passage Lockset Flat Ball Knob Satin Nickel US15
55029	Privacy Lockset Flat Ball Knob Satin Nickel US15
55030	Entry Lockset Flat Ball Knob Satin Nickel US15 KD/KW1
55031	Dummy Lockset Flat Ball Knob Satin Nickel US15

Finishes



US15 – Satin Nickel

Warranty

• Five Year Limited Warranty

