

Residential Electric Water Heaters



LOWBOY

ENHANCED HEATING ELEMENTS

 Dual 4500 watt copper elements for fast recovery and reliable operation.

PEX DIP TUBE

 Made from long-lasting PEX cross-linked polymer, maximizing hot water output.

HIGH ENERGY FACTORS

 Eco-friendly non-CFC foam insulation, heat traps, and other features combine to yield a higher Energy Factor that maximizes savings on operating costs.

ANODE ROD

 Our anode rods have a stainless steel core that extends the life of the anode rod allowing superior tank protection far longer than standard anode rods.

GLASS COATING

 Provides superior corrosion resistance compared to industry-standard glass lining.

DRAIN VALVE

- Our residential water heaters have a tamper-resistant drain valve.
- Uses a standard female hose fitting that allows for fast and easy draining during maintenance.

CODE COMPLIANCE

 Meets UBC, and ICC NationalCode and listed with CEC. Complies with the Federal Energy Conservation Standards effective April 16, 2015, in accordance with the Energy Policy and Conservation Act (EPCA), as amended.

CERTIFIED TO UL 174 FOR HOUSEHOLD ELECTRIC WATER HEATERS

CSA CERTIFIED AND ASME RATED T&P RELIEF VALVE

DESIGN-LISTED BY UNDERWRITER'S LABORATORIES

- Certified at 300 PSI test pressure and 150 PSI working pressure.
- Listed according to UL 174 standards governing storage tank-type electric water heaters.

6-YEAR LIMITED TANK AND PARTS WARRANTY

 For complete information, consult written warranty.



48-GALLON TOP CONNECT PRODUCT SHOWN








Residential Electric Water Heaters


				.					Dimensions in Inches		
Tank and Parts Warranty	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Uniform Energy Factor	Upper Element	tage Lower Element	Gallons Per Hour Recovery*	Height	Diameter	Approx. Shipping Weight (lbs.)
TOP CONNECT LOWBOY – Signature™											
6-year	E6-30L45DBTTP	28	26	43	0.89	4500	4500	21	30"	20"	90
6-Year	E6-30L45DTTP	28	26	44	0.9	4500	4500	21	31 1/4	24	115
6-year	E6-36L45DTTP	36	33	51	0.92	4500	4500	21	32"	24"	118
6-year	E6-40L45DBTTP	38	51	51	0.92	4500	4500	21	32"	23"	118
6-year	E6-50L45DBTTP	48	44	60	0.93	4500	4500	21	34"	26-1/2"	172

^{*}Based on 90° rise.

Male 3/4" water connections on 8" center.

Dimensions and specifications are subject to change without notice in accordance with our policy of continuous product improvement.





For technical information call (877) 817-6750. A. O. Smith Water Heaters reserves the right to make product changes or improvements without prior notice.