

OPTIONS**Flush Volume**

- 0.5 gpf (1.9 Lpf) (0.5)
- 1.0 gpf (3.8 Lpf) (1.0)
- 0.25 gpf (0.9 Lpf) (0.25)
- 3.5 gpf (13.2 Lpf) (3.5)

Finish

- Polished Chrome (CP)

Power Type

- Battery
- Hardwired (HW)

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- High Efficiency

Fixture Type

- Urinal

Fixture Connection

- Top Spud

Installation

- Exposed

Override

- Less (L/OR)

Control Stop

- Adjustable Ground Joint for Tek (XDT)
- No (XD)

Special Features

- Fits Zurn† valve bodies (Z)
- Less Logo (LL)

Specialty

- Retrofit

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- Satisfies LEED Credits
- cUPC Certified
- BREEAM Water Credit
- Green Globes Water Credit



Image for a standard G2 RESS-U shown

DESCRIPTION

G2 Exposed Sensor Urinal Retrofit Flushometer

FEATURES

- Valve shall be in compliance to the applicable sections of ASSE 1037

DOWNLOADS

- [Optima Plus Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)

cUPC Green Certified
UPC Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† Zurn® is a registered trademark of Zurco, Inc. Use of "Zurn" is for identification purposes only and does not imply affiliation, endorsement, or association between Sloan and Zurco, Inc.